

Mt Robson Visitors Centre ▼

Information

Date of Audit: 2016-07-19

Park Name: Cottonwood Island Park

Key Features: Picnic_Site, Trails

Location: Fraser Fort George, Prince George, Northern BC - Municipal : Park (Great Northern Circle Route)

Description: As this park is beside the river be aware that some paths are subject to erosion

Parking

2. Are an adequate number of accessible spaces provided? : N_A (Rating: 0)

3. Of the accessible spaces, is at least one a van accessible space?* : N_A (Rating: 0)

4. Are accessible spaces at least 2.4m wide with an access aisle at least 1.5m wide? Note: Two spaces may share an access aisle. : N_A (Rating: 0)

5. Are the access aisles marked to discourage parking in them? : N_A (Rating: 0)

6. Is the slope of the accessible parking spaces and access aisles no steeper than 1Â° in all directions? : Yes - Meets Standard (Rating: 1)

7. Does the access aisle adjoin an accessible route? : N_A (Rating: 0)

8. Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Note: The International Symbol of Accessibility is not required on the ground. : No (Rating: 0)

9. Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? Note: If parking serves multiple entrances, accessible parking should be dispersed. : N_A (Rating: 0)

2. What is the condition of the surface along this trail? : Moderate (Rating: 1)

Access Routes

Trails

Date of Audit : 2016-07-19

Name of Trail : Cottonwood Island Heritage Trail

Section of trail audited : from south parking lot to north parking lot

Weather condition during audit : Sunny





Clear Width

5. What is the typical trail width (mm)? : More_than_1525 (Rating: 0)

6. What is the narrowest trail width (mm)? : between_1525_-_1220

Comments/Description : tree roots

Comments/Description : 90% are more than 1220 mm apart

Comments/Description : coming off the bridge there is an 8' slope for 1400 mm

Recommendations : add gravel to sides and pack

Improvement Priority : Med

Estimated Cost : Low

Comments/Description : washouts on the sides of the bridge slope, 1800 mm apart

Recommendations : maintenance

Improvement Priority : Med

Estimated Cost : Low

Openings

11. Are there any gaps or grates present that have an opening greater than 13mm? : No (Rating: 0)

12. If gaps/grates are present, do they run perpendicular to the path of travel? : N_A (Rating: 0)

14. What is the maximum running slope on the trail? : Moderate_2_-_3 (Rating: 1)

Comments/Description : nice easy trail

Recommendations : add gravel and pack to reduce slope

Improvement Priority : Med

Estimated Cost : Med

16. What is the maximum cross slope on the trail? : Moderate_2_-_3 (Rating: 1)

Comments/Description : only two or three times briefly

Comments/Description : 90% of trail is 1 to 3' slope

Recommendations : add a few accessible benches

Improvement Priority : Low

Estimated Cost : Med

18. If the running slope is greater than 3°, are there resting intervals in the middle of the trail when the length exceeds 9.1m? : N_A (Rating: 0)

Comments/Description : occasional branches

Recommendations : prune

Improvement Priority : Med

Estimated Cost : Low

Comments/Description : the clear width of this trail is typically well over 1000 mm

Comments/Description : one only at the far end of this trail

Recommendations : install accessible benches

Improvement Priority : Med

Estimated Cost : Med

22. If yes, are the benches located approximately every 61m? : No_-_below_standard (Rating: 0)

23. Is the bench seat height between 485mm - 510mm? : N_A (Rating: 0)

Comments/Description : at each end of replica bridge

**Measurement
(mm)** : 1700

Comments/Description : to 2000 wide

27. For each section of the ramp, is the running slope no greater than 5°?

Note: Rises no greater than 76mm with a slope no steeper than 7° and rises no greater than 150mm with a slope no steeper than 6° are permitted when due to space limitations. : Yes_-_meets_standard (Rating: 1)

28. Is there a level landing that is at least 1525mm long and at least as wide as the ramp: At the top of the ramp? : Yes_-_meets_standard (Rating: 1)

29. At the bottom of the ramp? : Yes_-_meets_standard (Rating: 1)

30. Is there a level landing where the ramp changes direction that is at least 1525mm x 1525mm? : Yes_-_meets_standard (Rating: 1)

Comments/Description : long curve at park end, T junction at top with ample maneuvering room for people, dogs, strollers or wheelchairs

32. Is the top of the handrail gripping surface no less than 865mm and no greater than 965mm above the ramp surface? : No - _Below_ Standard (Rating: 0)

**Measurement
(mm) : 1000**

Comments/Description : see pictures

34. If there are obstructions, is the bottom of the gripping surface obstructed no more than 20%? : Yes - _Meets_ Standard (Rating: 1)

Stairs

35. Are there floors or surfaces connected only by stairs, not an elevator or ramp? : No (Rating: 0)

36. How many flights of stairs are there? : N_A

37. If there are less than a flight, how many stairs are there? : N_A

38. Do all stair treads have a horizontal strip at the edge that is: 40mm-60mm deep, colour contrasted & extends the full width of the step? : N_A (Rating: 0)

39. If the stairs are not enclosed, is there a tactile warning system present at the landing of entrance to stairs system? : N_A (Rating: 0)

40. Are there handrails on both sides of the stairs at a uniform height of 860mm-920mm above the front step? : N_A (Rating: 0)

41. Do the handrails extend horizontally at the top and bottom of each flight of stairs? : N_A (Rating: 0)

42. Are the handrails continuous around landings? : N_A (Rating: 0)

43. Are the handrails continuously graspable, without interruption by vertical supports, newel posts, or other construction elements which require repositioning the hands while ascending or descending? : N_A (Rating: 0)

44. Do the handrails have a graspable cross-section that is either circular with an outside diameter of 30mm-40mm or elliptical with an outside perimeter of 100mm-125mm? : N_A (Rating: 0)

Comments/Description : bridge with a view of the river

2. Is there sufficient clear ground space, a minimum of 915mm x 1220mm for the user to view the key features? : Yes - _Exceeds_ Standard

Comments/Description : bridge is 3 meters wide,

Comments/Description : rails are solid, boards are long way instead of across but gaps are less than 13 mm

4. What type of surface is the viewing area? : Boardwalk

Comments/Description : transition from gravel to boards is poor with lip exceeding 13 mm

Recommendations : add gravel and pack

Improvement Priority : Med

Estimated Cost : Low

5. Is there a clear space between 815mm - 1320mm above the ground, free of obstructions and extending the full width of clear space? : Yes_ - _Exceeds_Standard

Measurement (mm) : 2950

Comments/Description : overhanging branch

Recommendations : prune

Improvement Priority : Med

Estimated Cost : Low

Picnic Area

1. Are picnic tables provided? : No (Rating: 0)

2. How many accessible picnic tables are there? : N_A

3. If the picnic table is up to 2.7m long, is there one wheelchair seating space? : N_A (Rating: 0)

4. If the picnic table is longer than 2.7m, are there at least two wheelchair spaces provided? : N_A (Rating: 0)

5. Is there clear and level ground space, 915mm measured from back edge of seats/benches? : N_A (Rating: 0)

6. Do the accessible spaces have adequate knee clearance, 685mm high x 760mm wide x 430mm deep? : N_A (Rating: 0)

7. Is the ground surface surrounding the accessible picnic table firm and stable? : N_A (Rating: 0)

8. Is there a clear, level accessible route to the picnic table? : N_A (Rating: 0)

Shelters

1. Are there any camp shelters? : No (Rating: 0)

2. What is the slope at the entrance to the camp shelter? : N_A (Rating: 0)

3. What type of surface is in the camp shelter? : N_A

4. Is the shelter surface firm and stable? : N_A (Rating: 0)

5. Is there a clear, level accessible route to the camp shelter? : N_A (Rating: 0)

Comments/Description : one at the start

2. If yes, how many benches are there? : N_A

3. Is the bench seat height between 485mm - 510mm? : N_A (Rating: 0)

4. Is there a minimum of 915mm x 1220mm clear ground space beside the bench? : No_-_Below_Standard (Rating: 0)

5. Is there a clear, level accessible route to the bench? : No (Rating: 0)

**Measurement
(mm) :** 920

4. If there are operable parts, can they be operated using one hand, without tightly grasping, pinching, or twisting the wrist and with no more than 2.3kg of force? : No (Rating: 0)

Comments/Description : cannot be used with closed fist, bear proof

Comments/Description : on grass but level

Recommendations : relocate beside or on path or create packed level path and pad

Improvement Priority : Med

Estimated Cost : Med

Campfires & Grills

1. Is there an area for campfires? : No (Rating: 0)

2. Is there a minimum of 1220mm clear ground space on all sides? : N_A (Rating: 0)

3. Is the slope 3° or less in all directions? : N_A (Rating: 0)

4. Is the grill height between 380mm - 865mm above the ground? : N_A (Rating: 0)

5. Is the fire building surface height at least 230mm above the ground? : N_A (Rating: 0)

6. If there is a raised edge or wall around the fire building area, is the thickness less than 255mm? : N_A (Rating: 0)

7. Is there a clear, level accessible route to the campfire area? : N_A (Rating: 0)

1. Are any public washrooms located at the trail head or on the trail? : Yes_-_WASHROOMS_checklist_must_also_be_completed

Additional comments regarding assessment : This trail is typically flat or gentle running slopes. The paved path is in good condition with only a few cracks and roots. The gravel paths are also in typically good condition, some have gotten narrower over time due to vegetation creep. There is the occasional hanging branch that would be an issue for those that are visually impaired or not paying attention. The exception is any path near water. Those have been or will be subject to erosion. Some of them end abruptly with a steep fall into a ditch or the river. They need barriers please.

Suggestions for improvement of audit tool : When you answer no to the first question in a section it would be nice if the balance of the questions auto filled



Description of Photo 1 : Gravel erodes away over time creating a barrier getting on and off the bridge



Description of Photo 2 : Open grassy lawn with extra picnic tables with open ends that might be sort of accessible if you could wheel over the grass



Description of Photo 3 : Trail end needs a barrier please



Description of Photo 4 : Sort of accessible bench, bring bird seed, the chickadees will eat out of your hand

Washrooms

Date of Audit : 2016-07-19

Auditors Names : Cathy & Randy

Weather condition during audit : Sunny

Washroom # : 1

Description of washroom location : located near the parking lot beside the Railway museum

Type of Washroom : Out-house



1. If washrooms are available to the public, is at least one washroom designated as accessible? (Either one for each sex, or one unisex.) : Yes (Rating: 1)

Recommendations : install signs

Improvement Priority : Med

Estimated Cost : Low

Directional signage

2. Are there signs at inaccessible washrooms that give directions to accessible washrooms? : No (Rating: 0)

Recommendations : install signs

Improvement Priority : Med

Estimated Cost : Low

3. Is there an accessible route to the accessible washroom? : Yes (Rating: 1)

4. If not all washrooms are accessible, is there a sign at the accessible washroom with the International Symbol of Accessibility? : No (Rating: 0)

Recommendations : install sign

Improvement Priority : Med

Estimated Cost : Low

5. Do text characters contrast with their backgrounds? : N_A (Rating: 0)

6. Are text characters raised? : N_A (Rating: 0)

7. Is there Braille? : N_A (Rating: 0)

8. Is the sign mounted on the wall, on latch side of the door?

Note: Signs are permitted on the push side of doors with closers and without hold-open devices. : N_A (Rating: 0)

9. So the baseline of the lowest character is at least 1220mm above the floor and the baseline of the highest

character is no more than 1525mm above the floor?

Note: If the sign is at double doors with one active leaf, the sign should be on the inactive leaf; if both leaves are active, the sign should be on the wall to the right of the right leaf. : N_A (Rating: 0)

Interior doors

10. Is the door opening width at least 815mm clear, between the face of the door and the stop, when the door is open 90°? : Yes (Rating: 1)

**Measurement
(mm) : 840**

11. If there is a front approach to the pull side of the door, is there at least 455mm of maneuvering clearance beyond the latch side plus at least 1525mm clear depth? : N_A (Rating: 0)

12. On both sides of the door, is the floor surface of the maneuvering clearance level (no steeper than 1°)? : No (Rating: 0)

**Measurement
(angle °) : 7**

Comments/Description : approach is smooth and firm but steep

Recommendations : Decrease the slope, preferably to 1 degree

Improvement Priority : Med

Estimated Cost : Med

13. If the threshold is vertical is it no more than 6mm high?

Or : No (Rating: 0)

**Measurement
(mm) : 40**

Recommendations : Level pack the approach so it is flush with the floor

Improvement Priority : Med

Estimated Cost : Med

14. If the threshold is beveled, is it no more than 19mm high? : N_A (Rating: 0)

15. Is the door equipped with hardware that is operable with one hand and does not require tight grasping, pinching or twisting of the wrist? : Yes (Rating: 1)

16. Are the operable parts of the hardware no less than 865mm and no greater than 1220mm above the floor? : Yes (Rating: 1)

**Measurement
(mm) : 1200**

17. Can the door be opened easily, maximum 2.3kg of force?

Note: You can use a pressure gauge or fish scale to measure force. : Yes (Rating: 1)

Measurement

(kg) : 2

18. If the door has a closer, does it take at least 5 seconds to close from open position of 90° to a position of 12° from the latch? : N_A (Rating: 0)

19. If there are two doors in a series, e.g. vestibule, is the distance between the doors at least 1220mm plus the width of the doors when swinging into the space? : N_A (Rating: 0)

20. If there is a privacy wall and the door swings out, is there at least 610mm of maneuvering clearance beyond the door latch side and 1065mm to the privacy wall? : N_A (Rating: 0)

21. If there is a privacy wall and the door swings in, is there at least 610mm of maneuvering clearance beyond the door latch side and at least 1220mm to the privacy wall if there is no door closer or at least 1370mm if there is a door closer? : N_A (Rating: 0)

22. In a unisex washroom if the door swings in and over a clear floor space at an accessible fixture, is there a clear floor space at least 760mm x 1220mm beyond the swing of the door? : N_A (Rating: 0)

Toilet stall

23. Is there an individual accessible toilet stall? : Yes (Rating: 1)

24. Is the stall door opening width at least 815mm clear, between the face of the door and the stop, when the door is open 90°? : Yes (Rating: 1)

Measurement

(mm) : 840

25. If there is a front approach to the pull side of the stall door, is there at least 455mm of maneuvering clearance beyond the latch side plus 1525mm clear depth? : N_A (Rating: 0)

26. Is the door self-closing? : No (Rating: 0)

27. Are there door pulls on both sides of the door that are operable with one hand and do not require tight grasping pinching or twisting of the wrist?* : Yes (Rating: 1)

28. Is the lock operable with one hand and without tight grasping, pinching or twisting of the wrist? : No (Rating: 0)

Comments/Description : bolt is small and not easily operated with a closed fist to simulate arthritis

29. Are the operable parts of the door hardware mounted no less than 865mm and no greater than 1220mm above the floor? : Yes (Rating: 1)

Measurement

(mm) : 1200

30. Is the stall at least 1525mm wide? : No (Rating: 0)

Measurement

(mm) : 1500

31. If the toilet is wall hung, is the stall at least 1420mm deep?

Or : Yes (Rating: 1)

Measurement

(mm) : 1530

32. If the toilet is floor mounted, is the stall at least 1500mm deep? : Yes (Rating: 1)

Measurement

(mm) : 1530

If the door swings in, is the stall area beyond the swing of the door:

33. A minimum of 1525mm wide x 1420mm deep for wall hung toilet?

Or : N_A (Rating: 0)

34. A minimum of 1525mm wide x 1500mm deep for floor mounted toilet? : Yes (Rating: 1)

Measurement

(mm x mm) : 1500 x 1530

Toilet

35. Is the centerline of the toilet no less than 405mm and no greater than 455mm from the side wall or partition? : Yes (Rating: 1)

36. Is clearance provided around the toilet measuring at least 1525mm from the side wall and at least 1420mm from the rear wall? : Yes (Rating: 1)

From side wall

(mm) : 1500

From rear wall

(mm) : 1530

37. Is the height of the toilet no less than 430mm and no greater than 485mm above the floor measured to the top of the seat? : No (Rating: 0)

Measurement

(mm) : 385

Recommendations : raise the toilet

Improvement Priority : Med

Estimated Cost : Low

Grab bars

38. Is there a grab bar at least 1065mm long on the side wall? : No (Rating: 0)

Measurement
(mm) : 690

Recommendations : replace with a grab bar that meets or exceeds the standard

39. Is it located no more than 305mm from the rear wall? : Yes (Rating: 1)

Measurement
(mm) : 180

40. Does it extend at least 1370mm from the rear wall? : No (Rating: 0)

Measurement
(mm) : 870

41. Is it mounted no less than 840mm and no greater than 915mm above the floor to the top of the gripping surface? : Yes (Rating: 1)

Measurement
(mm) : 850

42. Is there at least 305mm clearance between the grab bar and protruding objects above? : No (Rating: 0)

43. Is there at least 38mm clearance between the grab bar and projecting objects below? : N_A (Rating: 0)

44. Is the space between the wall and the grab bar 38mm : Yes (Rating: 1)

Measurement
(mm) : 40

45. Is there a grab bar at least 915mm long on the rear wall? : No (Rating: 0)

Measurement
(mm) : 690

Recommendations : replace with a bar that meets or exceeds the standard

Improvement Priority : Med

Estimated Cost : Low

46. Does the grab bar extend at least 305mm from the centerline of the toilet on one side (side wall)? : No (Rating: 0)

Measurement
(mm) : 0

47. Does the grab bar extend at least 610mm on the other (open) side? : Yes (Rating: 1)

Measurement
(mm) : 690

48. Is the grab bar mounted no less than 840mm and no greater than 915mm above the floor to the top of

the gripping surface? : Yes (Rating: 1)

**Measurement
(mm) : 845**

**49. Are there at least 305mm clearance between the grab bar and protruding objects above? : N_A
(Rating: 0)**

**50. Are there at least 38mm clearance between the grab bar and projecting objects below? : N_A (Rating:
0)**

51. Is the space between the wall and the grab bar 38mm inches? : Yes (Rating: 1)

**Measurement
(mm) : 40**

Toilet flush controls

**52. If the flush control is hand operated, is the operable part located no higher than 1220mm above the
floor? : N_A (Rating: 0)**

**53. If the flush control is hand operated, can it be operated with one hand and without tight grasping,
pinching, or twisting of the wrist? : N_A (Rating: 0)**

54. Is the force required to activate the flush control no greater than 2.3kg? : N_A (Rating: 0)

55. Is the flush control on the open side of the toilet? : N_A (Rating: 0)

Toilet paper dispenser

**56. Is the toilet paper dispenser located no less than 180mm and no greater than 230mm from the front of
the toilet to the center line of the dispenser? : No (Rating: 0)**

**Measurement
(mm) : 500**

Comments/Description : too far away for some to reach without risking a fall

Recommendations : move to within standards

Improvement Priority : Med

Estimated Cost : Low

**57. Is the outlet of the dispenser: Located no less than 380mm and no greater than 1220mm above the
floor? : Yes (Rating: 1)**

**Measurement
(mm) : 550**

58. Is the dispenser located behind grab bars? : No (Rating: 0)

59. Does the dispenser allow continuous paper flow? : Yes (Rating: 1)

Sink

60. Does at least one sink have a clear floor space for a forward approach at least 760mm wide and 1220mm long? : N_A (Rating: 0)

61. Do no less than 430mm and no greater than 635mm of the clear floor space extend under the sink so that a person using a wheelchair can get close enough to reach the faucet? : N_A (Rating: 0)

62. Is the front of the sink or counter surface, whichever is higher, no more than 865mm above the floor? : N_A (Rating: 0)

63. Is there at least 685mm height clearance from the floor to the bottom of the sink that extends at least 205mm deep under the sink for knee clearance? : N_A (Rating: 0)

64. Is there toe clearance at least 230mm high?

Note: Space extending greater than 150mm beyond the available toe clearance at 230mm above the floor is not considered toe clearance. : N_A (Rating: 0)

65. Are pipes below the sink insulated or otherwise configured to protect against contact? : N_A (Rating: 0)

66. Can the faucet be operated without tight grasping, pinching, or twisting of the wrist? : N_A (Rating: 0)

67. Is the force required to activate the faucet no greater than 2.3 kg? : N_A (Rating: 0)

Washroom fixtures

68. Is there a clear path to at least one of each type of fixture, e.g. sink, hand dryer, garbage bin etc., that is at least 915mm wide? : N_A (Rating: 0)

69. Is there clear floor space available for a person in a wheelchair to turn around, i.e. a circle at least 1525mm in diameter or a T-shaped space within a 1525mm square? : N_A (Rating: 0)

Mirror

70. If the mirror is over a sink or countertop, is the bottom edge of the reflecting surface no higher than 1015mm above the floor?

Or : N_A (Rating: 0)

71. If the mirror is not over the sink or countertop, is the bottom edge of the reflecting surface no higher than 890mm above the floor? : N_A (Rating: 0)

Coat hook

72. If there is a coat hook, is it no less than 380mm and no greater than 1220mm above the floor? : N_A (Rating: 0)

Soap dispenser

Are the operable parts of the soap dispenser within one of the following reach ranges:

73. Above sinks or counters no less than 510mm and no greater than 635mm deep: no higher than

1120mm above the floor?

Or : N_A (Rating: 0)

74. Above sinks less than 510mm deep: no higher than 1220mm above the floor?

Or : N_A (Rating: 0)

75. Not over an obstruction: no higher than 1220mm above the floor? : N_A (Rating: 0)**Hand dryer/Towel dispenser**

Are the operable parts of the hand dryer or towel dispenser within one of the following reach ranges:

76. Above sinks or counters no less than 510mm and no greater than 635mm deep: no higher than 1120mm above the floor?

Or : N_A (Rating: 0)

77. Above sinks less than 510mm deep: no higher than 1220mm above the floor?

Or : N_A (Rating: 0)

78. Not over an obstruction: no higher than 1220mm above the floor? : N_A (Rating: 0)**79. Can the operable parts of the hand dryer or towel dispenser be operated without tight grasping, pinching or twisting of the wrist? : N_A (Rating: 0)****80. Is the force required to activate the hand dryer or towel dispenser no greater than 2.3kg? : N_A (Rating: 0)****Controls - light switches****81. Is there a clear floor space at least 760mm wide by at least 1220mm long for a forward or parallel approach? : N_A (Rating: 0)****82. Are the operable parts no higher than 1220mm above the floor? : N_A (Rating: 0)****83. Can the control be operated with one hand and without tight grasping, pinching, or twisting of the wrist? : N_A (Rating: 0)**

Additional comments regarding assessment: : The acces route to this outhouse is smooth and stable but steep at 7 degrees. It needs to be leveled as much as possible and packed flush with the concrete floor for maximum accessibility.



Description of Photo 1 : Note the lip that happens with erosion over time



Description of Photo 2 : There is a 7.5 degree slope to get in to this outhouse. It needs to be reduced as much as possible.



Description of Photo 3 : Toilet is too low.

Camping

Water Access

Goods and Services

Date of Audit : 2016-07-19

Weather condition during audit : Sunny

Description of building & service : Picnic shelter at parking lot by railway museum



Parking

1. Is parking provided for the public? : Yes (Rating: 1)

Comments/Description : unmarked gravel, no signs

Recommendations : install designated accessible parking signs

Improvement Priority : Med

Estimated Cost : Low

2. Are an adequate number of accessible spaces provided? : N_A (Rating: 0)

3. Of the accessible spaces, is at least one a van accessible space?* : N_A (Rating: 0)

4. Are accessible spaces at least 2.4m wide with an access aisle at least 1.5m wide? Note: Two spaces may share an access aisle. : N_A (Rating: 0)

5. Are the access aisles marked to discourage parking in them? : N_A (Rating: 0)

6. Is the slope of the accessible parking spaces and access aisles no steeper than 1° in all directions? : N_A (Rating: 0)

7. Does the access aisle adjoin an accessible route? : N_A (Rating: 0)

8. Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Note: The International Symbol of Accessibility is not required on the ground. : N_A (Rating: 0)

9. Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? Note: If parking serves multiple entrances, accessible parking should be dispersed. : N_A (Rating: 0)

From: : parking lot

To: : picnic shelter

General

1. Is there at least one route from site arrival points (parking, loading zone, bus stop etc) that does not require the use of stairs? : Yes (Rating: 1)

2. What is the condition of the surface along this route? : Good

Comments/Description : older asphalt, some patching ridges, tree roots and cracks

Surface

3. Is the surface firm and stable? : Yes (Rating: 1)

4. What is the type of surface? : Asphalt

Comments/Description : Part of the path to the shelter is newer and smoother

Clear Width

5. What is the typical route width (mm)? : between_1525_-_1220

6. What is the narrowest route width (mm)? : between_1220_-915 (Rating: 1)

Obstacles

7. If the route is concrete, asphalt or boardwalk, are there any obstacles that exceed 13mm from the surface? : No (Rating: 0)

8. If yes, are the obstacles at least 1220mm apart? : N_A (Rating: 0)

9. If the route is anything other than concrete, asphalt or boardwalk, are there any obstacles that exceed

25mm from the surface? : N_A (Rating: 0)

10. If yes, are the obstacles at least 1220mm apart? : N_A (Rating: 0)

Openings

11. Are there any gaps or grates present that have an opening greater than 13mm? : No (Rating: 0)

12. If gaps/grates are present, do they run perpendicular to the path of travel? : N_A (Rating: 0)

Running Slope

13. What is the typical running slope on the route? : Moderate_2_-_3 (Rating: 1)

14. What is the maximum running slope on the route? : Moderate_2_-_3 (Rating: 1)

Cross Slope

15. What is the typical cross slope on the route? : Flat_Gentle_1_or_less

16. What is the maximum cross slope on the route? : Moderate_2_-_3 (Rating: 1)

Resting Intervals

17. Are there resting intervals at the top and bottom of a route where the grade exceeds 3°? : N_A (Rating: 0)

18. If the running slope is greater than 3°, are there resting intervals in the middle of the route when the length exceeds 9.1m? : N_A (Rating: 0)

Protruding Objects

19. Is there a minimum of 2030mm vertical clearance for users to safely pass along the route without coming into contact with overhanging obstacles? : Yes_-_exceeds_standard

20. Is there a minimum of 100mm horizontal clearance for users to safely pass along the route without coming into contact with side obstacles? : Yes_-_exceeds_standard

Benches

21. Are there any benches along the route? : No (Rating: 0)

22. If yes, are the benches located approximately every 61m? : N_A (Rating: 0)

23. Is the bench seat height between 485mm - 510mm? : N_A (Rating: 0)

Ramps

24. Is there is a ramp? : No (Rating: 0)

25. Is the ramp at least 915mm wide?

Note: If there are handrails, measure between the handrails. : N_A (Rating: 0)

26. Is the surface stable, firm and slip resistant? : N_A (Rating: 0)

27. For each section of the ramp, is the running slope no greater than 5°?

Note: Rises no greater than 76mm with a slope no steeper than 7° and rises no greater than 150mm with a slope no steeper than 6° are permitted when due to space limitations. : N_A (Rating: 0)

28. Is there a level landing that is at least 1525mm long and at least as wide as the ramp: At the top of the ramp? : N_A (Rating: 0)

29. At the bottom of the ramp? : N_A (Rating: 0)

30. Is there a level landing where the ramp changes direction that is at least 1525mm x 1525mm? : N_A (Rating: 0)

31. If the ramp has a rise higher than 150mm are there handrails on both sides? : N_A (Rating: 0)

32. Is the top of the handrail gripping surface no less than 865mm and no greater than 965mm above the ramp surface? : N_A (Rating: 0)

33. Is the handrail gripping surface continuous and not obstructed along the top or sides? : N_A (Rating: 0)

34. If there are obstructions, is the bottom of the gripping surface obstructed no more than 20%? : N_A (Rating: 0)

Stairs

35. Are there floors or surfaces connected only by stairs, not an elevator or ramp? : No (Rating: 0)

36. How many flights of stairs are there? : N_A

37. If there are less than a flight, how many stairs are there? : N_A

38. Do all stair treads have a horizontal strip at the edge that is: 40mm-60mm deep, colour contrasted & extends the full width of the step? : N_A (Rating: 0)

39. If the stairs are not enclosed, is there a tactile warning system present at the landing of entrance to stairs system? : N_A (Rating: 0)

40. Are there handrails on both sides of the stairs at a uniform height of 860mm-920mm above the front step? : N_A (Rating: 0)

41. Do the handrails extend horizontally at the top and bottom of each flight of stairs? : N_A (Rating: 0)

42. Are the handrails continuous around landings? : N_A (Rating: 0)

43. Are the handrails continuously graspable, without interruption by vertical supports, newel posts, or other construction elements which require repositioning the hands while ascending or descending? : N_A (Rating: 0)

44. Do the handrails have a graspable cross-section that is either circular with an outside diameter of 30mm-40mm or elliptical with an outside perimeter of 100mm-125mm? : N_A (Rating: 0)

1. Does the accessible entrance provide direct access to the main floor, lobby and elevator? : Yes (Rating: 1)

Interior Accessible Route

2. Are all public spaces on at least one accessible route? : Yes (Rating: 1)

3. Is the route stable, firm and slip-resistant? : Yes (Rating: 1)

5. If the route is greater than 61m in length and less than 1525mm wide, is there a passing space no less than 1525mm x 1525mm? : N_A (Rating: 0)

6. Is the running slope no steeper than 3°

**Note: If the running slope is steeper than 3°, treat as a ramp, see ramps section on the next page. : Yes -
_Meets_Standard (Rating: 1)**

7. Is the cross slope no steeper than 1°? : Yes - _Meets_Standard (Rating: 1)

Ramps

8. Is there is a ramp? : No (Rating: 0)

9. Is the ramp at least 915mm wide?

Note: If there are handrails, measure between the handrails. : N_A (Rating: 0)

10. Is the surface stable, firm and slip resistant? : N_A (Rating: 0)

11. For each section of the ramp, is the running slope no greater than 5°?

Note: Rises no greater than 76mm with a slope no steeper than 7° and rises no greater than 150mm with a slope no steeper than 6° are permitted when due to space limitations. : N_A (Rating: 0)

12. Is there a level landing that is at least 1525mm long and at least as wide as the ramp:

At the top of the ramp? : N_A (Rating: 0)

13. At the bottom of the ramp? : N_A (Rating: 0)

**14. Is there a level landing where the ramp changes direction that is at least 1525mm x 1525mm? : N_A
(Rating: 0)**

15. If the ramp has a rise higher than 150mm are there handrails on both sides? : N_A (Rating: 0)

16. Is the top of the handrail gripping surface no less than 865mm and no greater than 965mm above the ramp surface? : N_A (Rating: 0)

17. Is the handrail gripping surface continuous and not obstructed along the top or sides? : N_A (Rating: 0)

**18. If there are obstructions, is the bottom of the gripping surface obstructed no more than 20%? : N_A
(Rating: 0)**

Stairs

19. Are there floors or surfaces connected only by stairs, not an elevator or ramp? : No (Rating: 0)
20. How many flights of stairs are there? : N_A
21. If there are less than a flight, how many stairs are there? : N_A
22. Do all stair treads have a horizontal strip at the edge that is: 40mm-60mm deep, colour contrasted & extends the full width of the step? : N_A (Rating: 0)
23. If the stairs are not enclosed, is there a tactile warning system present at the landing of entrance to stairs system? : N_A (Rating: 0)
24. Are there handrails on both sides of the stairs at a uniform height of 860mm-920mm above the front step? : N_A (Rating: 0)
25. Do the handrails extend horizontally at the top and bottom of each flight of stairs? : N_A (Rating: 0)
26. Are the handrails continuous around landings? : N_A (Rating: 0)
27. Are the handrails continuously graspable, without interruption by vertical supports, newel posts, or other construction elements which require repositioning the hands while ascending or descending? : N_A (Rating: 0)
28. Do the handrails have a graspable cross-section that is either circular with an outside diameter of 30mm-40mm or elliptical with an outside perimeter of 100mm-125mm? : N_A (Rating: 0)

Platform lifts

29. Is there a lift? : No (Rating: 0)
30. If a lift is provided, can it be used without assistance from others? : N_A (Rating: 0)
31. Is there a clear floor space at least 760mm wide by at least 1220mm long for a person using a wheelchair to approach and reach the controls to use the lift? : N_A (Rating: 0)
32. Are the lift controls no less than 380mm and no greater than 1220mm above the floor? : N_A (Rating: 0)
33. Is there a clear floor space at least 760mm wide by at least 1220mm long inside the lift? : N_A (Rating: 0)
34. If there is an end door, is the clear opening width at least 815mm? : N_A (Rating: 0)
35. If there is a side door, is the clear opening width at least 1065mm? : N_A (Rating: 0)

Directional signage

If there are signs designating permanent rooms and spaces not likely to change over time, e.g. room numbers and letters, room names, and exit signs:

36. Do text characters contrast with their backgrounds? : N_A (Rating: 0)
37. Are text characters raised? : N_A (Rating: 0)

38. Is there Braille? : N_A (Rating: 0)

39. Is the sign mounted on the wall, on latch side of the door?

Note: Signs are permitted on the push side of doors with closers and without hold-open devices. : N_A (Rating: 0)

40. So the baseline of the lowest character is at least 1220mm above the floor and the baseline of the highest character is no more than 1525mm above the floor?

Note: If the sign is at double doors with one active leaf, the sign should be on the inactive leaf; if both leaves are active, the sign should be on the wall to the right of the right leaf. : N_A (Rating: 0)

If there are signs that provide direction to or information about interior spaces:

41. Do text characters contrast with their background? : N_A (Rating: 0)

42. Is the sign mounted so that characters are at least 1015mm above the floor? : N_A (Rating: 0)

Interior doors

43. Is the door opening width at least 815mm clear, between the face of the door and the stop, when the door is open 90°? : N_A (Rating: 0)

44. If there is a front approach to the pull side of the door, is there at least 455mm of maneuvering clearance beyond the latch side plus at least 1525mm clear depth? : N_A (Rating: 0)

45. On both sides of the door, is the floor surface of the maneuvering clearance level (no steeper than 1°)? : N_A (Rating: 0)

46. If the threshold is vertical is it no more than 6mm high?

Or : N_A (Rating: 0)

47. If the threshold is beveled, is it no more than 19mm high? : N_A (Rating: 0)

48. Is the door equipped with hardware that is operable with one hand and does not require tight grasping, pinching or twisting of the wrist? : N_A (Rating: 0)

49. Are the operable parts of the hardware no less than 865mm and no greater than 1220mm above the floor? : N_A (Rating: 0)

50. Can the door be opened easily, maximum 2.3kg of force?

Note: You can use a pressure gauge or fish scale to measure force. : N_A (Rating: 0)

51. If the door has a closer, does it take at least 5 seconds to close from open position of 90° to a position of 12° from the latch? : N_A (Rating: 0)

Rooms & spaces

52. Are aisles and pathways to goods and services, and to one of each type of sales and service counters, at least 915mm wide? : Yes_-_Meets_Standard (Rating: 1)

Comments/Description : ample room between tables for wheelchairs or other mobility aids

53. Are floor surfaces stable, firm and slip resistant? : Yes (Rating: 1)

Controls - light switches, security & intercom systems, emergency/alarm boxes, etc.

54. Is there a clear floor space at least 760mm wide by at least 1220mm long for a forward or parallel approach? : N_A (Rating: 0)

55. Are the operable parts no higher than 1220mm above the floor? : N_A (Rating: 0)

56. Can the control be operated with one hand and without tight grasping, pinching, or twisting of the wrist? : N_A (Rating: 0)

57. Do fire alarm systems have both flashing lights and audible signals? : N_A (Rating: 0)

Sales & Service Counters

Is there a portion of at least one of each type of counter that is:

58. No higher than 915mm above the floor? : N_A (Rating: 0)

59. At least 915mm long? : N_A (Rating: 0)

60. Is there a clear floor space at least 760mm wide by at least 1220mm long for a forward approach?

Or : N_A (Rating: 0)

61. Is there a clear floor space at least 1220mm wide by at least 760mm long for a parallel approach? : N_A (Rating: 0)

Seating: At dining surfaces (restaurants, cafeterias, bars, etc.)

62. Are at least 5%, but no fewer than 1, of seating and standing spaces accessible for people who use wheelchairs? : N_A (Rating: 0)

63. Is there a route at least 915mm wide to accessible seating? : N_A (Rating: 0)

64. At the accessible space(s), is the top of the accessible surface no less than 710mm and no greater than 865mm above the floor? : N_A (Rating: 0)

65. Does it extend no less than 430mm and no greater than 635mm under the surface? : N_A (Rating: 0)

66. Is there knee space at least 685mm high and at least 760mm wide? : N_A (Rating: 0)

Water Fountains

1. Is there a water fountain? : No (Rating: 0)

2. Does it have a lever or push bar control on the front or both sides? : N_A (Rating: 0)

3. Is the spout opening height between 750mm - 915mm above the ground? : N_A (Rating: 0)

4. Is there a minimum width of 800mm clearance space directly in front of the water fountain? : N_A
(Rating: 0)

5. Is there a clear, level accessible route to the water fountain? : N_A (Rating: 0)

Trash & Recycling Receptacles

6. Are there any trash &/or recycling receptacles? : Yes (Rating: 1)

7. Is the approach to the receptacle level, with no-step? : Yes (Rating: 1)

8. If there are operable parts, is their height between 380mm - 1220mm above the ground? : Yes (Rating: 1)

Measurement
(mm) : 920

9. If there are operable parts, can they be operated using one hand, without tightly grasping, pinching, or twisting the wrist and with no more than 2.3kg of force? : No (Rating: 0)

Comments/Description : bear proof

10. Is there a clear, level accessible route to the trash/recycling receptacle? : Yes (Rating: 1)

Comments/Description : across grass

Public Telephones

11. Are there telephones available to the public? : No (Rating: 0)

12. Does at least one public telephone have a minimum of 800mm wide and 800mm deep unobstructed access in front of the telephone? : N_A (Rating: 0)

13. Does it have a minimum vertical clearance of 715mm under the directory shelf? : N_A (Rating: 0)

14. Is the coin slot no higher than 1200mm above the ground? : N_A (Rating: 0)

15. Is the telephone identified as being usable by persons in wheelchairs and persons with a hearing impairment? : N_A (Rating: 0)

16. Does it have an adjacent shelf to hold a telecommunication device for the deaf (TDD)? : N_A (Rating: 0)

17. Does it have a handset incorporating a hearing aid coupler coil? : N_A (Rating: 0)

1. Are any public washrooms located at goods & services? : Yes -
_WASHROOMS_checklist_must_also_be_completed

Additional comments regarding assessment: : The picnic shelter was accessible, it would have been nice if the tables had been too. There is otherwise plenty of room to accommodate wheelchairs. The trails were typically wide and flat with minimal barriers, particularly the paved path. The gravel paths had some intrusion of vegetation and there was some overhanging branches, easily fixed by pruning. In a forested area like this it is to be expected. Anything near the water is subject to erosion in high water years. A couple of paths needed barriers to alert people to the danger of falling in the river.

Suggestions for improvement of audit tool: : Auto-fill is so nice

Description of Photo 1 : Lots of room to get around both tables, concrete tops to discourage vandalism, wish one was an accessible style



Description of Photo 2 : Garbage can nearest the picnic shelter is beside a path, could be reached by an agile wheelchair user.



Description of Photo 3 : Parking lot has a paved area for wheelchair transition near the replica bridge but if grass was eliminated and gravel added and packed all along there is enough room between posts to make the trail and park much more accessible for all



Description of Photo 4 : Eroded end of the trail, needs a barrier for the inattentive pokemon go players.